



PERAKUAN PEMATUHAN STANDARD (BAHAN BINAAN)

Dengan ini disahkan bahawa

HIAP TECK HARDWARE SDN BHD (276336-A)

LOT 6096, JALAN HJ.ABD MANAN
BATU 5 1/2, JALAN MERU
41050 KLANG, SELANGOR

Telah menjalani ujian di makmal yang diiktiraf sebagaimana butiran di bawah

No. Kelulusan PPS : 2-07190205	
Nama & Alamat Kilang	
RIZHAO MEDIUM SECTION MILL CO., LTD NO.600, BINHAI ROAD 276806 RIZHAO CITY SHANDONG PROVINCE, CHINA	
Kategori Produk	Negara Pembuat
IRON AND STEEL PRODUCTS	CHINA
No. Sijil Produk / Laporan Ujian : PC001779	
Tempoh Sah Perakuan Pematuhan Standard	23 Apr 2024 sehingga 22 Apr 2025
Jenis produk Bahan Binaan : (Rujuk Lampiran A untuk butiran terperinci)	

SR NAZIR MUHAMAD NOR
PENGURUS BESAR
BAHAGIAN PEMATUHAN KUALITI BINAAN

SIJIL INI ADALAH CETAKAN KOMPUTER DAN TIDAK MEMERLUKAN TANDATANGAN

LAMPIRAN A

No. Kelulusan PPS : **2-07190205**
 No. Permohonan : **PPSi_0424000186**
 Nama Syarikat / Pengimport : **HIAP TECK HARDWARE SDN BHD**

NO.	NAMA PRODUK	STANDARD PRODUK	JENAMA	SAIZ / DIMENSI	MODEL NO.	GRED
1	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 150 X 150 X 7 X 10, 175 X 175 X 7.5 X 11, 194 X 150 X 6 X 9, 200 X 150 X 6 X 9, 200 X 200 X 8 X 12, 200 X 200 X 12 X 12, 200 X 200 X 10 X 16, 200 X 204 X 12 X 12, 208 X 202 X 10 X 16, 244 X 175 X 7 X 11, 244 X 252 X 11 X 11	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
2	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 198 X 99 X 4.5 X 7, 200 X 100 X 4.5 X 7, 248 X 124 X 5 X 8	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
3	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 200 X 100 X 5.5 X 8	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
4	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 248 X 249 X 8 X 13, 250 X 175 X 7 X 11, 250 X 250 X 11 X 11, 250 X 250 X 8 X 13, 250 X 250 X 9 X 14, 250 X 250 X 14 X 14, 250 X 255 X 14 X 14, 294 X 200 X 8 X 12, 294 X 302 X 12 X 12, 298 X 201 X 9 X 14, 298 X 299 X 9 X 14	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)

5	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 250 X 125 X 5 X 8	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
6	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 250 X 125 X 6 X 9, 298 X 149 X 5.5 X 8,	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
7	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 300 X 150 X 5.5 X 8, 300 X 150 X 6.5 X 9	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
8	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM)= 300 X 200 X 8 X 12, 300 X 200 X 9 X 14, 300 X 300 X 9 X 14, 300 X 300 X 10 X 15, 300 X 300 X 11 X 17, 300 X 300 X 12 X 12, 300 X 300 X 15 X 15, 300 X 305 X 15 X 15, 304 X 301 X 11 X 17, 336 X 249 X 8 X 12, 338 X 351 X 13 X 13, 340 X 250 X 9 X 14, 344 X 348 X 10 X 16	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
9	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 344 X 354 X 16 X 16, 350 X 250 X 8 X 12, 350 X 250 X 9 X 14, 350 X 350 X 10 X 16, 350 X 350 X 12 X 19, 350 X 350 X 13 X 13, 350 X 350 X 16 X 16, 350 X 350 X 19 X 19, 350 X 357 X 19 X 19, 386 X 299 X 9 X 14	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
10	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 346 X 174 X 6 X 9, 350 X 175 X 6 X 9, 350 X 175 X 7 X 11, 350 X 175 X 8 X 13, 354 X 176 X 8 X 13	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)

11	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 388 X 402 X 15 X 15, 390 X 300 X 10 X 16, 394 X 398 X 11 X 18, 394 X 405 X 18 X 18, 400 X 300 X 9 X 14, 400 X 300 X 10 X 16, 400 X 400 X 11 X 18, 400 X 400 X 13 X 21, 400 X 400 X 15 X 15, 400 X 400 X 18 X 18	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
12	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 396 X 199 X 7 X 11, 400 X 200 X 7 X 11, 400 X 200 X 8 X 13, 400 X 200 X 9 X 15	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
13	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 400 X 400 X 18 X 28, 400 X 400 X 21 X 21, 400 X 408 X 21 X 21, 414 X 405 X 18 X 28, 434 X 299 X 10 X 15, 440 X 300 X 11 X 18, 446 X 302 X 13 X 21, 450 X 300 X 10 X 15, 450 X 300 X 11 X 18	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
14	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 404 X 201 X 9 X 15, 446 X 199 X 8 X 12, 450 X 200 X 8 X 12, 450 X 200 X 9 X 14, 450 X 200 X 10 X 17	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
15	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (M) = 450 X 300 X 13 X 21, 482 X 300 X 11 X 15, 488 X 300 X 11 X 18, 494 X 302 X 13 X 21, 500 X 300 X 11 X 15, 500 X 300 X 11 X 18, 500 X 300 X 13 X 21, 582 X 300 X 12 X 17	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
16	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (M) = 456 X 201 X 10 X 17, 496 X 199 X 9 X 14, 500 X 200 X 9 X 14, 500 X 200 X 10 X 16, 500 X 200 X 11 X 19, 506 X 201 X 11 X 19	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)

17	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) =588 X 300 X 12 X 20, 594 X 302 X 14 X 23, 600 X 300 X 12 X 17, 600 X 300 X 12 X 20, 600 X 300 X 14 X 23, 692 X 300 X 13 X 20, 700 X 300 X 13 X 20, 700 X 300 X 13 X 24	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
18	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X WEB THICKNESS (MM) X FLANGE THICKNESS (MM) = 596 X 199 X 10 X 15, 600 X 200 X 10 X 15, 600 X 200 X 11 X 17, 600 X 200 X 12 X 20, 600 X 200 X 13 X 23, 606 X 201 X 12 X 20, 612 X 202 X 13 X 23,	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
19	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X UNIT WEIGHT (KGM) =152 X 152 X 23, 152 X 152 X 30, 152 X 152 X 37, 203 X 203 X 46, 203 X 203 X 46.1, 203 X 203 X 52, 203 X 203 X 60, 203 X 203 X 71, 203 X 203 X 86,254 X 254 X 73, 254 X 254 X 89, 254 X 254 X 107, 254 X 254 X 132, 254 X 254 X 167, 305 X 305 X 97, 305 X 305 X 118, 305 X 305 X 137, 305 X 305 X 158, 305 X 305 X 198, 305 X 305 X 240, 305 X 305 X 283, 356 X 368 X 129, 356 X 368 X 153, 356 X 368 X 177, 356 X 368 X 202, 356 X 406 X 235, 356 X 406 X 235.1	UNIVERSAL COLUMN	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
20	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X UNIT WEIGHT (KG/M) 203 X 102 X 15,	UNIVERSAL BEAMS	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)

21	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X UNIT WEIGHT (KG/M) =203 X 102 X 23, 203 X 133 X 25, 203 X 133 X 30, 254 X 102 X 22, 254 X 102 X 25, 254 X 102 X 28, 254 X 146 X 31, 254 X 146 X 37, 254 X 146 X 43, 305 X 102 X 25, 305 X 102 X 28, 305 X 102 X 33, 305 X 165 X 40, 305 X 165 X 46, 305 X 165 X 54, 356 X 127 X 33, 356 X 127 X 39, 356 X 171 X 45, 356 X 171 X 51, 356 X 171 X 57, 356 X 171 X 67, 406 X 140 X 39, 406 X 140 X 46, 406 X 178 X 54, 406 X 178 X 60, 406 X 178 X 67, 406 X 178 X 74, 457 X 152 X 52, 457 X 152 X 60	UNIVERSAL BEAMS	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
22	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X UNIT WEIGHT (KG/M) =457 X 152 X 67, 457 X 152 X 74, 457 X 152 X 82, 457 X 191 X 67, 457 X 191 X 74, 457 X 191 X 82, 457 X 191 X 89, 457 X 191 X 98, 533 X 210 X 82, 533 X 210 X 92, 533 X 210 X 101, 533 X 210 X 109, 533 X 210 X 122, 610 X 229 X 101, 610 X 229 X 113, 610 X 229 X 125, 610 X 229 X 140, 686 X 254 X 125, 686 X 254 X 140, 686 X 254 X 152, 686 X 254 X 170	UNIVERSAL BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
23	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH (MM) X WIDTH (MM) X UNIT WEIGHT (KG/M) = 610 X 305 X 149, 610 X 305 X 179, 610 X 305 X 238,	UNIVERSAL BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)

24	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	<p>DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 100 X 100 X 6 X 8, 125 X 125 X 6.5 X 9, 148 X 100 X 6 X 9, 150 X 100 X 6 X 9, 150 X 150 X 7 X 10, 175 X 175 X 7.5 X 11, 194 X 150 X 6 X 9, 200 X 150 X 6 X 9, 200 X 200 X 8 X 12, 200 X 200 X 12 X 12, 200 X 200 X 10 X 16, 200 X 204 X 12 X 12, 208 X 202 X 10 X 16, 244 X 175 X 7 X 11, 244 X 252 X 11 X 11, 248 X 249 X 8 X 13, 250 X 250 X 11 X 11, 250 X 250 X 8 X 13, 250 X 250 X 9 X 14, 250 X 250 X 14 X 14, 250 X 255 X 14 X 14, 294 X 200 X 8 X 12, 298 X 201 X 9 X 14, 298 X 299 X 9 X 14, 294 X 302 X 12 X 12, 300 X 200 X 8 X 12, 300 X 200 X 9 X 14, 300 X 300 X 9 X 14, 300 X 300 X 10 X 15, 300 X 300 X 11 X 17, 300 X 300 X 12 X 12, 300 X 300 X 15 X 15, 300 X 305 X 15 X 15, 304 X 301 X 11 X 17, 310 X 305 X 15 X 20, 310 X 310 X 20 X 20, 336 X 249 X 8 X 12, 338 X 351 X 13 X 13, 350 X 250 X 8 X 12, 340 X 250 X 9 X 14, 350 X 250 X 9 X 14, 344 X 348 X 10 X 16, 344 X 354 X 16 X 16, 350 X 350 X 10 X 16, 350 X 350 X 12 X 19, 350 X 350 X 13 X 13, 350 X 350 X 16 X 16, 350 X 350 X 19 X 19, 350 X 357 X 19 X 19, 386 X 299 X 9 X 14, 390 X 300 X 10 X 16, 400 X 300 X 9 X 14, 400 X 300 X 10 X 16, 388 X 402 X 15 X 15, 394 X 398 X 11 X 18, 394 X 405 X 18 X 18, 400 X 400 X 11 X 18, 400 X 400 X 13 X 21, 400 X 400 X 15 X 15, 400 X 400 X 18 X 18, 400 X 400 X 18 X 28, 400 X 400 X 21 X 21, 400 X 408 X 21 X 21, 406 X 403 X 16 X 24, 414 X 405 X 18 X 28, 428 X 407 X 20 X 35, 458 X 417 X 30 X 50, 498 X 432 X 45 X 70, 446 X 302 X 13 X 21, 434 X 299 X 10 X 15, 440 X 300 X 11 X 18, 450 X 300 X 10 X 15, 450 X 300 X 11 X 18, 450 X 300 X 13 X 21, 482 X 300 X 11 X 15, 488 X 300 X 11 X 18, 494 X 302 X 13 X 21, 500 X 300 X 11 X 15,</p>	H-BEAM	S235= JR , DELIVERY CONDITION = +AR (AS ROLLED)
----	---	----------------------	---	---	--------	---

				500 X 300 X 11 X 18, 500 X 300 X 13 X 21 582 X 300 X 12 X 17, 588 X 300 X 12 X 20, 594 X 302 X 14 X 23, 600 X 300 X 12 X 17, 600 X 300 X 12 X 20 600 X 300 X 14 X 23, 692 X 300 X 13 X 20, 700 X 300 X 13 X 20, 700 X 300 X 13 X 24, 708 X 302 X 15 X 28, 792 X 300 X 14 X 22, 800 X 300 X 14 X 22, 800 X 300 X 14 X 26		
25	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 150 X 75 X 5 X 7, 198 X 99 X 4.5 X 7, 200 X 100 X 4.5 X 7, 248 X 124 X 5 X 8, 250 X 125 X 5 X 8,	H-BEAM	S235= JR , DELIVERY CONDITION = +AR (AS ROLLED)
26	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 200 X 100 X 5.5 X 8, 250 X 125 X 6 X 9, 298 X 149 X 5.5 X 8, 300 X 150 X 5.5 X 8, 300 X 150 X 6.5 X 9, 346 X 174 X 6 X 9, 350 X 175 X 6 X 9, 350 X 175 X 7 X 11, 350 X 175 X 8 X 13, 354 X 176 X 8 X 13, 396 X 199 X 7 X 11, 400 X 150 X 8 X 13, 400 X 200 X 7 X 11, 400 X 200 X 8 X 13, 400 X 200 X 9 X 15 404 X 201 X 9 X 15, 446 X 199 X 8 X 12, 450 X 200 X 8 X 12, 450 X 200 X 9 X 14, 450 X 200 X 10 X 17, 456 X 201 X 10 X 17, 496 X 199 X 9 X 14, 500 X 200 X 9 X 14, 500 X 200 X 10 X 16, 500 X 200 X 11 X 19, 506 X 201 X 10 X 19, 506 X 201 X 11 X 19, 596 X 199 X 10 X 15, 600 X 200 X 10 X 15, 600 X 200 X 11 X 17, 600 X 200 X 12 X 20, 600 X 200 X 13 X 23, 606 X 201 X 12 X 20, 612 X 202 X 13 X 23,	H-BEAM	S235= JR , DELIVERY CONDITION = +AR (AS ROLLED)

27	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 152 X 152 X23, 152 X 152 X 30, 152 X 152 X 37, 203 X 203 X 46, 203 X 203 X 46.1, 203 X 203 X 52, 203 X 203 X 60, 203 X 203 X 54, 203 X 203 X 71, 203 X 203 X 86, 203 X 203 X 100, 254 X 254 X 63, 254 X 254 X 71, 254 X 254 X 73, 254 X 254 X 80, 254 X 254 X 85, 254 X 254 X 89, 254 X 254 X 101, 254 X 254 X 107, 254 X 254 X 115, 254 X 254 X 132, 254 X 254 X 149, 254 X 254 X 167, 305 X 305 X 97, 305 X 305 X 107, 305 X 305 X 118, 305 X 305 X 126, 305 X 305 X 137, 305 X 305 X 149, 305 X 305 X 158, 305 X 305 X 179, 305 X 305 X 186, 305 X 305 X 198, 305 X 305 X 203, 305 X 305 X 223, 305 X 305 X 240, 305 X 305 X 253, 305 X 305 X 283, 356 X 368 X 109, 356 X 368 X 129, 356 X 368 X 133, 356 X 368 X 148, 356 X 368 X 153, 356 X 368 X 162, 356 X 368 X 177, 356 X 368 X 197, 356 X 368 X 202	UNIVERSAL COLUMN	S275= J0 , DELIVERY CONDITION = +AR (AS ROLLED)
28	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 100 X 100 X 6 X 8, 125 X 125 X 6.5 X 9, 148 X 100 X 6 X 9, 150 X 100 X 6 X 9, 800 X 300 X 14 X 22, 800 X 300 X 14 X 26	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
29	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 150 X 75 X 5 X 7	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
30	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 400 X 150 X 8 X 13	H-BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)

31	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 762 X 267 X 134, 762 X 267 X 147, 762 X 267 X 160, 762 X 267 X 173, 762 X 267 X 185, 762 X 267 X 197, 762 X 267 X 220, 838 X 292 X 176, 838 X 292 X 194, 838 X 292 X 211, 838 X 292 X 226, 838 X 292 X 227,	UNIVERSAL BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
32	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 914 X 305 X 201, 914 X 305 X 224, 914 X 305 X 238, 914 X 305 X 253, 914 X 305 X 272, 914 X 305 X 289	UNIVERSAL BEAM	S275= JR , DELIVERY CONDITION = +AR (AS ROLLED)
33	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 457 X 152 X 52, 457 X 152 X 60, 457 X 152 X 67, 457 X 152 X 74, 457 X 152 X 82, 457 X 191 X 67, 457 X 191 X 74, 457 X 191 X 82, 457 X 191 X 89, 457 X 191 X 98, 457 X 191 X 106, 457 X 280 X 113, 457 X 280 X 128, 533 X 165 X 66, 533 X 165 X 75, 533 X 165 X 85, 533 X 210 X 82, 533 X 210 X 92 533 X 210 X 101, 533 X 210 X 109, 533 X 210 X 122, 533 X 210 X 138, 610 X 178 X 82, 610 X 178 X 92, 610 X 229 X 101, 610 X 229 X 113, 610 X 229 X 125, 610 X 229 X 140, 610 X 229 X 154, 610 X 229 X 172, 686 X 254 X 125, 686 X 254 X 140 686 X 254 X 152, 686 X 254 X 170, 686 X 254 X 191, 686 X 254 X 236, 762 X 267 X 134, 762 X 267 X 147, 762 X 267 X 160, 762 X 267 X 173	UNIVERSAL BEAM	S355= J0 , DELIVERY CONDITION = +AR (AS ROLLED)
34	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 610 X 305 X 149, 610 X 305 X 179, 610 X 305 X 238,	UNIVERSAL BEAM	S355= J0 , DELIVERY CONDITION = +AR (AS ROLLED)

35	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 152 X 152 X 23, 152 X 152 X 30, 152 X 152 X 37, 203 X 203 X 46, 203 X 203 X 46.1, 203 X 203 X 52, 203 X 203 X 60, 203 X 203 X 54, 203 X 203 X 71, 203 X 203 X 86, 203 X 203 X 100, 254 X 254 X 63, 254 X 254 X 71, 254 X 254 X 73 254 X 254 X 80, 254 X 254 X 85, 254 X 254 X 89, 254 X 254 X 101, 254 X 254 X 107, 254 X 254 X 115, 254 X 254 X 132, 254 X 254 X 149, 254 X 254 X 167, 305 X 305 X 97, 305 X 305 X 107, 305 X 305 X 118, 305 X 305 X 126, 305 X 305 X 137, 305 X 305 X 149, 305 X 305 X 158, 305 X 305 X 179 305 X 305 X 186, 305 X 305 X 198, 305 X 305 X 203, 305 X 305 X 223, 305 X 305 X 240, 305 X 305 X 253, 305 X 305 X 283, 356 X 368 X 109, 356 X 368 X 129, 356 X 368 X 133, 356 X 368 X 148, 356 X 368 X 153, 356 X 368 X 162, 356 X 368 X 177, 356 X 368 X 197, 356 X 368 X 202	UNIVERSAL COLUMN	S355= J0 , DELIVERY CONDITION = +AR (AS ROLLED)
----	---	----------------------	---	--	------------------	---

36	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	<p>DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 203 X 102 X 23, 203 X 133 X 25, 203 X 133 X 30, 254 X 102 X 22, 254 X 102 X 25, 254 X 102 X 28, 254 X 146 X 31, 254 X 146 X 33, 254 X 146 X 37, 254 X 146 X 39, 254 X 146 X 43, 254 X 146 X 45, 305 X 102 X 25, 305 X 102 X 28, 305 X 102 X 33, 305 X 127 X 37, 305 X 127 X 42, 305 X 127 X 48, 305 X 165 X 39, 305 X 165 X 40, 305 X 165 X 46, 305 X 165 X 54, 356 X 127 X 33, 356 X 127 X 39, 356 X 171 X 45, 356 X 171 X 51, 356 X 171 X 57, 356 X 171 X 67 406 X 140 X 39, 406 X 140 X 46, 406 X 178 X 54, 406 X 178 X 60, 406 X 178 X 67, 406 X 178 X 74, 406 X 178 X 85, 457 X 152 X 52, 457 X 152 X 60, 457 X 152 X 67, 457 X 152 X 74, 457 X 152 X 82, 457 X 191 X 67, 457 X 191 X 74, 457 X 191 X 82, 457 X 191 X 89, 457 X 191 X 98, 457 X 191 X 106 457 X 280 X 113, 457 X 280 X 128, 533 X 165 X 66, 533 X 165 X 75, 533 X 165 X 85, 533 X 210 X 82, 533 X 210 X 92, 533 X 210 X 101, 533 X 210 X 109, 533 X 210 X 122, 533 X 210 X 138, 610 X 178 X 82, 610 X 178 X 92, 610 X 229 X 101, 610 X 229 X 113, 610 X 229 X 125, 610 X 229 X 140 610 X 229 X 154, 610 X 229 X 172, 686 X 254 X 125, 686 X 254 X 140, 686 X 254 X 152, 686 X 254 X 170, 686 X 254 X 191, 686 X 254 X 236, 762 X 267 X 134, 762 X 267 X 147, 762 X 267 X 160, 762 X 267 X 173, 762 X 267 X 185 762 X 267 X 197, 762 X 267 X 220, 838 X 292 X 176, 838 X 292 X 194, 838 X 292 X 211, 838 X 292 X 226, 838 X 292 X 227</p>	UNIVERSAL BEAM	S355= JR , DELIVERY CONDITION = +AR (AS ROLLED)
37	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	<p>DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 254 X 146 X 24,</p>	UNIVERSAL BEAM	S355= JR , DELIVERY CONDITION = +AR (AS ROLLED)

38	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 254 X 203 X 49, 254 X 203 X 58, 254 X 203 X 67, 610 X 305 X 149, 610 X 305 X 179, 610 X 305 X 238, 914 X 305 X 201, 914 X 305 X 224, 914 X 305 X 238, 914 X 305 X 253, 914 X 305 X 272, 914 X 305 X 289	UNIVERSAL BEAM	S355= JR , DELIVERY CONDITION = +AR (AS ROLLED)
----	--	----------------------	---	--	----------------	---

39	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	<p>DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 100 X 100 X 6 X 8, 125 X 125 X 6.5 X 9, 148 X 100 X 6 X 9, 150 X 100 X 6 X 9, 150 X 150 X 7 X 10, 175 X 175 X 7.5 X 11, 194 X 150 X 6 X 9, 200 X 150 X 6 X 9, 200 X 200 X 8 X 12, 200 X 200 X 12 X 12, 200 X 200 X 10 X 16, 200 X 204 X 12 X 12, 208 X 202 X 10 X 16, 244 X 175 X 7 X 11, 244 X 252 X 11 X 11, 248 X 249 X 8 X 13, 250 X 250 X 11 X 11, 250 X 250 X 8 X 13, 250 X 250 X 9 X 14, 250 X 250 X 14 X 14, 250 X 255 X 14 X 14, 294 X 200 X 8 X 12, 298 X 201 X 9 X 14, 298 X 299 X 9 X 14, 294 X 302 X 12 X 12, 300 X 200 X 8 X 12, 300 X 200 X 9 X 14, 300 X 300 X 9 X 14, 300 X 300 X 10 X 15, 300 X 300 X 11 X 17, 300 X 300 X 12 X 12 300 X 300 X 15 X 15, 300 X 305 X 15 X 15, 304 X 301 X 11 X 17, 310 X 305 X 15 X 20, 310 X 310 X 20 X 20, 336 X 249 X 8 X 12, 338 X 351 X 13 X 13, 350 X 250 X 8 X 12, 340 X 250 X 9 X 14, 350 X 250 X 9 X 14, 344 X 348 X 10 X 16, 344 X 354 X 16 X 16, 350 X 350 X 10 X 16, 350 X 350 X 12 X 19, 350 X 350 X 13 X 13, 350 X 350 X 16 X 16, 350 X 350 X 19 X 19, 350 X 357 X 19 X 19, 386 X 299 X 9 X 14, 390 X 300 X 10 X 16, 400 X 300 X 9 X 14, 400 X 300 X 10 X 16, 388 X 402 X 15 X 15, 394 X 398 X 11 X 18, 394 X 405 X 18 X 18, 400 X 400 X 11 X 18, 400 X 400 X 13 X 21, 400 X 400 X 15 X 15, 400 X 400 X 18 X 18, 400 X 400 X 18 X 28, 400 X 400 X 21 X 21 400 X 408 X 21 X 21, 406 X 403 X 16 X 24, 414 X 405 X 18 X 28, 428 X 407 X 20 X 35, 458 X 417 X 30 X 50, 498 X 432 X 45 X 70, 446 X 302 X 13 X 21, 434 X 299 X 10 X 15, 440 X 300 X 11 X 18 450 X 300 X 10 X 15, 450 X 300 X 11 X 18, 450 X 300 X 13 X 21, 482 X 300 X 11 X 15, 488 X 300 X 11 X 18, 494 X 302 X 13 X 21, 500 X 300 X</p>	H-BEAM	S355= JR , DELIVERY CONDITION = +AR (AS ROLLED)
----	---	----------------------	---	---	--------	---

				11 X 15, 500 X 300 X 11 X 18, 500 X 300 X 13 X 21 582 X 300 X 12 X 17, 588 X 300 X 12 X 20, 594 X 302 X 14 X 23, 600 X 300 X 12 X 17, 600 X 300 X 12 X 20 600 X 300 X 14 X 23, 692 X 300 X 13 X 20, 700 X 300 X 13 X 20, 700 X 300 X 13 X 24, 708 X 302 X 15 X 28, 792 X 300 X 14 X 22, 800 X 300 X 14 X 22, 800 X 300 X 14 X 26		
40	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 150 X 75 X 5 X 7, 198 X 99 X 4.5 X 7, 200 X 100 X 4.5 X 7, 248 X 124 X 5 X 8, 250 X 125 X 5 X 8,	H-BEAM	S355= JR , DELIVERY CONDITION = +AR (AS ROLLED)
41	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 200 X 100 X 5.5 X 8, 250 X 125 X 6 X 9, 298 X 149 X 5.5 X 8, 300 X 150 X 5.5 X 8, 300 X 150 X 6.5 X 9, 346 X 174 X 6 X 9, 350 X 175 X 6 X 9, 350 X 175 X 7 X 11, 350 X 175 X 8 X 13, 354 X 176 X 8 X 13, 396 X 199 X 7 X 11, 400 X 150 X 8 X 13, 400 X 200 X 7 X 11, 400 X 200 X 8 X 13, 400 X 200 X 9 X 15 404 X 201 X 9 X 15, 404 X 201 X 9 X 15, 446 X 199 X 8 X 12, 450 X 200 X 8 X 12, 450 X 200 X 9 X 14, 450 X 200 X 10 X 17, 456 X 201 X 10 X 17, 496 X 199 X 9 X 14, 500 X 200 X 9 X 14, 500 X 200 X 10 X 16, 500 X 200 X 11 X 19, 506 X 201 X 10 X 19, 506 X 201 X 11 X 19, 596 X 199 X 10 X 15, 600 X 200 X 10 X 15, 600 X 200 X 10 X 15, 600 X 200 X 11 X 17, 600 X 200 X 12 X 20, 600 X 200 X 13 X 23,	H-BEAM	S355= JR , DELIVERY CONDITION = +AR (AS ROLLED)

42	HOT ROLLED SECTIONS OF NON-ALLOY STRUCTURAL STEEL	MS EN 10025-2 : 2011	H	DEPTH X WIDTH X WEB THICKNESS X FLANGE THICKNESS (MM) = 152 X 152 X 23, 152 X 152 X 30, 152 X 152 X 37, 203 X 203 X 46, 203 X 203 X 46.1, 203 X 203 X 52, 203 X 203 X 60, 203 X 203 X 54, 203 X 203 X 71, 203 X 203 X 86, 203 X 203 X 100, 254 X 254 X 63, 254 X 254 X 71, 254 X 254 X 73, 254 X 254 X 80, 254 X 254 X 85, 254 X 254 X 89, 254 X 254 X 101, 254 X 254 X 107, 254 X 254 X 115, 254 X 254 X 132, 254 X 254 X 149, 254 X 254 X 167, 305 X 305 X 97, 305 X 305 X 107, 305 X 305 X 118, 305 X 305 X 126, 305 X 305 X 137, 305 X 305 X 149, 305 X 305 X 158, 305 X 305 X 179, 305 X 305 X 186, 305 X 305 X 198, 305 X 305 X 203, 305 X 305 X 223, 305 X 305 X 240, 305 X 305 X 253, 305 X 305 X 283, 356 X 368 X 109, 356 X 368 X 129, 356 X 368 X 133, 356 X 368 X 148, 356 X 368 X 153, 356 X 368 X 162, 356 X 368 X 177, 356 X 368 X 197, 356 X 368 X 202	UNIVERSAL COLUMN	S355= JR , DELIVERY CONDITION = +AR (AS ROLLED)
----	---	----------------------	---	--	------------------	---